

Bar Refrigeration

TDR72-RISZ1-L-B-SSS-2

🇬🇧 Keg Chiller / Dispenser, Black Ext, 3 Solid Swing Doors



Dimensions	
External Width (mm)	1829
External Depth (mm)	631
External Height (mm)	882
Exclusions	Depth does not include 35 mm for door handles. Height does not include 7 mm for leg levelers or 400 mm for draft tower.
Gross Volume (Litres)	660
Unpackaged Weight (kg)	164
Packaged Weight (kg)	179
Internal Capacity for Keg (L x D x H mm)	1433 x 476 x 783
Supplied with	Levelling Screws. Optional castors sold seperately.

Build	
Door Description	3 Solid Swing Doors
Exterior Construction	Black powder coated steel front. Matching black coated Aluminium sides & rear. Stainless steel countertop.
Interior Construction	Stainless Steel
Air Intake Position	Front
Ventilation Position	Front
Clearance Required	Zero back and sides
Cord Length (Meters)	3.04
Internal Lighting	LED
Standard w/ Locks	Standard

Technical	
Temperature Range	0.5 : 3.3°C
Refrigerant	R290
Voltage/Frequency/Phase	220-240V/50-60Hz/1
Amps	1.3
Defrost Type	Auto



Specifications subject to change without notice.
Chart dimensions rounded up to the next whole millimeter (inches rounded up to the 1/8")

UK & Ireland
EMEA
Australia

0800 783 2049
[+41 61 563 07 05](tel:+41615630705)
[+61 2 9619 9999](tel:+61296199999)

TFIUK@truemfg.com
TrueCHCustomerService@truemfg.com
TrueRefAus@truemfg.com



TDR72-RISZ1-L-B-SSS-2

Technical drawings of the 24-inch wide, 48-inch high, 18-inch deep condensing unit. The drawings include a top view, a front view, and a side view. The top view shows a rectangular unit with two circular access ports on the left side, each with a diameter of 1 3/4 inches. The front view shows the unit's profile with a door opening on the right side. The side view shows the unit's depth and the location of the power cord exit. Dimensions are provided in inches and millimeters.

Top View Dimensions:

- Overall Width: 56 13/32" [1433]
- Overall Height: 43 19/32" [1107]
- Distance between access ports: 32" [813]
- Distance from left edge to first access port: 16 3/4" [426]
- Distance from first access port to second access port: 20" [508]
- Distance from second access port to right edge: 20" [508]
- Distance from top edge to first access port: 1 3/8" [35]
- Distance from top edge to second access port: 4 31/32" [126]
- Distance from top edge to bottom edge: 18 3/4" [476]
- Distance from bottom edge to right edge: 18 3/4" [476]
- Radius of bottom right corner: R18 31/32" [482]
- Drain Access: Ø 1" [25]

Front View Dimensions:

- Overall Width: 72" [1829]
- Overall Height: 31 11/16" [805]
- Distance from top edge to bottom edge: 2 7/32" [56]
- Distance from left edge to right edge: 11 19/32" [294]
- Distance from left edge to door opening: 19 5/8" [498]
- Door Opening: 16 9/32" [414] X 28 3/16" [716]
- Distance from bottom edge to right edge: 25/32" [20]

Side View Dimensions:

- Overall Width: 24 21/32" [626]
- Overall Height: 24 27/32" [631]
- Distance from top edge to bottom edge: 20 3/4" [527]
- Distance from left edge to right edge: 30 27/32" [783]
- Distance from bottom edge to right edge: 22 3/4" [578]
- Distance from top edge to right edge: 26 13/32" [670]
- Distance from bottom edge to right edge: 3 15/16" [100]
- Distance from top edge to right edge: 4 5/16" [110]
- Power Cord Exit: 18 1/2" [470]
- Distance from bottom edge to right edge: 19 7/16" [494]
- Distance from left edge to right edge: 10 31/32" [278]
- Distance from bottom edge to right edge: 6" [152]



Chart dimensions rounded up to the next whole millimeter (inches rounded up to the 1/8")

TFIUK@truemfg.com
TrueCHCustomerService@truemfg.com
TrueRefAus@truemfg.com

